

# Universal Primer Sealer #MX205



Muralo Universal Primer Sealer is a 100% acrylic, VOC compliant, interior & exterior, stain killing primer-sealer. It has outstanding adhesion to hard and glossy surfaces. Blocks most household stains, environmentally safe, spatter-resistant. Superior leveling allows for smoother Semi-gloss and High-gloss top coats. Universal's improved formula also offers lower sheen and outstanding hiding!



- Interior/exterior 100% acrylic primer
- Available in quarts, gallons, 2 gallons and 5 gallons
- High hiding
- Great flow & leveling
- Tremendous adhesion
- Blocks out most household stains

<b>Recommended Uses:</b>	For interior and exterior use on previously painted or unpainted wood, aluminum, plaster, concrete and masonry, drywall, galvanized metal, tile, Formica®, and glass.
<b>Surface Preparation:</b>	All surfaces must be clean and free from dirt, dust, grease, oil, peeling paint and mildew. A white powdery deposit (efflorescence) often found on masonry surfaces should be completely removed with a stiff wire brush.
<b>Application:</b>	Can apply by brush, roller, or spray. For best results use a synthetic bristle. <b>Roller:</b> 3/8 to 1/2 inch nap gives best results <b>Sprayer:</b> An 8 to 12 inch fan at 1 foot is ideal for airless and can be obtained with a tip size from .018 to .021 inches. Conventional spray, best results are obtained with air nozzle orifice sizes from .04 to .07 inches and pressures from 30 to 70 psi. Fluid nozzle orifice size should be .07 to .11 inches.
<b>Specification:</b>	<p><b><u>Wood Previously Painted:</u></b>  <b>Primer:</b> Muralo #2205, Universal Primer Sealer  <b>Finish:</b> 1 or 2 coats appropriate Muralo finish paint.</p> <p><b><u>New Staining Wood:</u></b>  <b>Primer:</b> Use Muralo 2201, Cedar Solution and/or X-200 Oil Base primer over new wood subject to tannin bleed, such as cedar and red wood.  <b>Finish:</b> 1 or 2 coats appropriate Muralo finish paint</p> <p><b><u>Ferrous metal, New, unpainted or rusty:</u></b>  <b>Primer:</b> Use Muralo Anti-Rust Primers  <b>Finish:</b> 1 or 2 coats appropriate Muralo finish paint</p> <p><b><u>Drywall, plaster or masonry, painted or unpainted:</u></b>  <b>Primer:</b> Muralo #2205, Universal Primer Sealer  <b>Finish:</b> 1 or 2 coats appropriate Muralo finish paint</p> <p><b><u>Aluminum or galvanized metal: Painted or unpainted:</u></b>  (Note New galvanized metal should be allowed to weather for 6 months prior to coating)  <b>Primer:</b> Muralo #2205, Universal Primer Sealer  <b>Finish:</b> 1 or 2 coats appropriate Muralo finish paint</p>
<b>Coverage:</b>	Approximately 400 sq. ft. per gallon
<b>Dry Time:</b>	(75°F, 50%RH) To touch 1 hour; To recoat 2 hours
<b>Thinning:</b>	Not recommended.
<b>V.O.C. (V.O.S.)</b>	Max. 50gms./ltr. Or 0.42 lbs./gal.
<b>Packaging:</b>	Quart, gallon and five gallon containers
<b>Colors:</b>	White. May be tinted with up to 4 ounces of universal colorant per gallon
<b>Generic Type:</b>	Acrylic-Latex
<b>Finish:</b>	Matte
<b>Weight Per Gal.:</b>	10.62 pounds
<b>Solids Content:</b>	By volume 30% - 35% By Weight 40% - 45%
<b>Recommended Film Thickness:</b>	Wet: 3.5 – Mils Dry: 1.5 Mils
<b>Cautions:</b>	Keep out of reach of children. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from freezing. Do not apply when temperature is below 40°F.

**DISCLAIMER:**

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

**NOTICE:** Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYL.